



Gerade-Verschraubung

Rohr - Ø	SW	Best.-Nr.	Typ	Preis
4	9	4040	GVS- 4 V	1,84
6	11	4041	GVS- 6 V	1,94
8	12	4042	GVS- 8 V	2,51
10	17	4043	GVS-10 V	3,58



Gerade-Schottverschraubung

Rohr - Ø	SW	Best.-Nr.	Typ	Preis
4	12	4016	GSS- 4 V	2,71
6	14	4017	GSS- 6 V	2,97
8	17	4018	GSS- 8 V	3,68
10	19	4019	GSS-10 V	5,73



Gerade Einschraub-Verschraubung, zylindrisch

Anschluß	Rohr - Ø	SW	Best.-Nr.	Typ	Preis
G 1/8"	4	14	2760	GEZ- 184 V	1,15
G 1/8"	6	14	2761	GEZ- 186 V	1,18
G 1/8"	8	14	2762	GEZ- 188 V	1,61
G 1/4"	6	19	2763	GEZ- 146 V	1,69
G 1/4"	8	19	2764	GEZ- 148 V	1,82
G 1/4"	10	19	2765	GEZ-1410 V	2,33



Gerade Einschraub-Verschraubung, konisch


Anschluß	Rohr - Ø	SW	Best.-Nr.	Typ	Preis
R 1/8"	4	10	4000	GES- 184 V	1,07
R 1/8"	6	11	4001	GES- 186 V	1,10
R 1/8"	8	12	4002	GES- 188 V	1,28
R 1/4"	6	14	4003	GES- 146 V	1,30
R 1/4"	8	14	4004	GES- 148 V	1,69
R 1/4"	10	17	4005	GES-1410 V	1,97
R 3/8"	8	17	4008	GES- 388 V	2,30

NEU



Gerade Aufschraub-Verschraubung

Anschluß	Rohr - Ø	SW	Best.-Nr.	Typ	Preis
G 1/8" i	4	14	4010	GAS-184 V	1,41
G 1/8" i	6	14	4011	GAS-186 V	1,46
G 1/8" i	8	14	4012	GAS-188 V	1,69
G 1/4" i	6	19	4013	GAS-146 V	1,76
G 1/4" i	8	19	4014	GAS-148 V	1,99



Winkel-Verschraubung

Rohr - Ø	SW	Best.-Nr.	Typ	Preis
4	7	4064	WVS- 4 V	2,07
6	9	4065	WVS- 6 V	2,15
8	12	4066	WVS- 8 V	3,14
10	14	4067	WVS-10 V	4,55

Betriebsdruck (PN): max. 60 bar - Material: Ms. vernickelt

Auf Anfrage auch bis Gewinde 1/2" und Rohr-Ø 18 mm lieferbar.