

**Winkel-Einschraub-Verschraubung, konisch**

Anschluß	Rohr - Ø	SW	Best.-Nr.	Typ	Preis
R 1/8"	4	7	4020	WES- 184 V	1,69
R 1/8"	6	9	4021	WES- 186 V	1,79
R 1/8"	8	12	4022	WES- 188 V	2,28
R 1/4"	6	9	4023	WES- 146 V	2,07
R 1/4"	8	12	4024	WES- 148 V	2,15
R 1/4"	10	14	4025	WES-1410 V	3,53

**Winkel-Aufschraub-Verschraubung - mit Klemmring**

Anschluß	Rohr - Ø	SW	Best.-Nr.	Typ	Preis
G 1/8" i	4	8	2786	WAS- 184 V	2,22
G 1/8" i	6	9	2787	WAS- 186 V	2,28
G 1/8" i	8	11	2788	WAS- 188 V	3,07
G 1/4" i	6	11	2789	WAS- 146 V	2,53
G 1/4" i	8	13	2790	WAS- 148 V	3,12
G 1/4" i	10	13	2791	WAS-1410 V	3,91

**Winkel-Schwenkverschraubung, zylindrisch**

Anschluß	Rohr - Ø	SW	Best.-Nr.	Typ	Preis
G 1/8"	6	14	4026	WSS- 186 V	2,84
G 1/8"	8	14	4027	WSS- 188 V	3,04
G 1/4"	6	17	4028	WSS- 146 V	3,30
G 1/4"	8	17	4029	WSS- 148 V	3,58

**Schwenkringstück einfach, ohne Hohlschraube**

Anschluß	Rohr - Ø	Best.-Nr.	Typ	Preis
G 1/8"	6	4036	SRS- 186 V	1,99
G 1/8"	8	4037	SRS- 188 V	2,10
G 1/4"	6	4038	SRS- 146 V	2,20
G 1/4"	8	4039	SRS- 148 V	2,30

**T-Verschraubung**

Rohr - Ø	SW	Best.-Nr.	Typ	Preis
4	10	4070	TVS- 4 V	3,40
6	12	4071	TVS- 6 V	3,63
8	14	4072	TVS- 8 V	4,50
10	19	4073	TVS-10 V	6,77

**T-Einschraub-Verschraubung, konisch**

Anschluß	Rohr - Ø	SW	Best.-Nr.	Typ	Preis
R 1/8"	4	7	4030	TES- 184 V	2,74
R 1/8"	6	9	4031	TES- 186 V	2,76
R 1/8"	8	12	4032	TES- 188 V	3,55
R 1/4"	6	9	4033	TES- 146 V	3,20
R 1/4"	8	12	4034	TES- 148 V	3,68
R 1/4"	10	14	4035	TES-1410 V	5,22

**Überwurfmutter für Schneidringverschraubungen**

Rohr - Ø	Gewinde	SW	Best.-Nr.	Typ	Preis
4	M 8x1,0	10	4045	UWS- 4 V	0,41
6	M 10x1,0	12	4046	UWS- 6 V	0,43
8	M 12x1,0	14	4047	UWS- 8 V	0,51
10	M 16x1,5	19	4048	UWS-10 V	0,72

Verschlusskegel siehe Seite 99.

Betriebsdruck (PN): max. 60 bar - Material: Ms. vernickelt

Auf Anfrage auch bis Gewinde 1/2" und Rohr-Ø 18 mm lieferbar.

