

T-Stück 3 x Außengewinde konisch, Ms. 58 vernickelt

Anschluß 1	Anschluß 2+3	Best.-Nr.	Typ	Preis
R M5 a	R M5 a	4798	TAG- M5 V	2,45
R 1/8" a	R 1/8" a	0561	TAG- 18 V	2,05
R 1/4" a	R 1/4" a	0562	TAG- 14 V	2,91
R 3/8" a	R 3/8" a	0563	TAG- 38 V	4,88
R 1/2" a	R 1/2" a	0564	TAG- 12 V	5,80
R 3/4" a	R 3/4" a	4799	TAG- 34 V	7,57
R 1" a	R 1" a	4800	TAG- 10 V	12,02

**T-Stück 3 x Außengewinde konisch, mit Innenkonus, Ms. 58**


Anschluß 1	Anschluß 2+3	Best.-Nr.	Typ	Preis
R 1/8" a	R 1/8" a	3191	TAK- 18	2,40
R 1/4" a	R 1/4" a	3192	TAK- 14	3,12
R 3/8" a	R 3/8" a	3193	TAK- 38	5,01
R 1/2" a	R 1/2" a	3194	TAK- 12	6,54




verwendbar für Schlauchtülle mit Überwurfmutter auf Seite 119.

T-Stück 1 x Innen-, 2 x Außengewinde konisch, Ms. 58 vern.

Anschluß 1+3	Anschluß 2	Best.-Nr.	Typ	Preis
R M5 a	G M5 i	4802	TAI- M5 V	1,99
R 1/8" a	G 1/8" i	0565	TAI- 18 V	2,17
R 1/4" a	G 1/4" i	0566	TAI- 14 V	3,04
R 3/8" a	G 3/8" i	0567	TAI- 38 V	4,88
R 1/2" a	G 1/2" i	0568	TAI- 12 V	5,80
R 3/4" a	G 3/4" i	4803	TAI- 34 V	7,57
R 1" a	G 1" i	4804	TAI- 10 V	12,02

**T-Stück 2 x Innen-, 1 x Außengewinde konisch, Ms. 58 vern.**

Anschluß 1+3	Anschluß 2	Best.-Nr.	Typ	Preis
G M5 i	R M5 a	4806	TIA- M5 V	1,99
G 1/8" i	R 1/8" a	0569	TIA- 18 V	2,17
G 1/4" i	R 1/4" a	0570	TIA- 14 V	3,04
G 3/8" i	R 3/8" a	0571	TIA- 38 V	4,88
G 1/2" i	R 1/2" a	0572	TIA- 12 V	5,80
G 3/4" i	R 3/4" a	4807	TIA- 34 V	7,57
G 1" i	R 1" a	4808	TIA- 10 V	12,02

**L-Stück 1 x Innen-, 2 x Außengewinde konisch, Ms. 58 vern.**

Anschluß 1	Anschluß 2+3	Best.-Nr.	Typ	Preis
G M5 i	R M5 a	4810	LAI- M5 V	1,99
G 1/8" i	R 1/8" a	1665	LAI- 18 V	2,17
G 1/4" i	R 1/4" a	1666	LAI- 14 V	3,04
G 3/8" i	R 3/8" a	1667	LAI- 38 V	4,88
G 1/2" i	R 1/2" a	1668	LAI- 12 V	5,80
G 3/4" i	R 3/4" a	4811	LAI- 34 V	7,57
G 1" i	R 1" a	4812	LAI- 10 V	12,02

**L-Stück 2 x Innen-, 1 x Außengewinde konisch, Ms. 58 vern.**

Anschluß 1	Anschluß 2+3	Best.-Nr.	Typ	Preis
R M5 a	G M5 i	4814	LIA- M5 V	1,99
R 1/8" a	G 1/8" i	0573	LIA- 18 V	2,17
R 1/4" a	G 1/4" i	0574	LIA- 14 V	3,04
R 3/8" a	G 3/8" i	0575	LIA- 38 V	4,88
R 1/2" a	G 1/2" i	0576	LIA- 12 V	5,80
R 3/4" a	G 3/4" i	4815	LIA- 34 V	7,57
R 1" a	G 1" i	4816	LIA- 10 V	12,02

